

PDA-GS0531W

5" MTK6761 Quad Core 2.0GHz
Handheld Terminal



Features:

- MTK6761 Quad Core 2.0GHz Processor
- 5.0 Inch IPS Capacitive Touch Screen
- Android 10.0 OS, Support Google Play
- 3900 mAh, Detachable Battery
- Honeywell 3603, 1D/2D Barcode Scanner
- Support Fast Charging >5V/2A
- 500 mAh Spare Battery

Specifications:

Performance

Chipset	MTK6761 4G Quad Core 2.0GHz	OS	Android 10.0 OS, support Google Play
RAM	2GB Ram; Max 4GB optional	Power Supply	3900 mAh, detachable battery
ROM	16GB Rom; Max 64GB optional		

Display

LCD	5 Inch IPS, 16: 9	Screen	Multi-touch Capacitive screen
Resolution	720*1280		

I/O Ports

USB	1*TYPE-C, Support fast charging >5V/2A	Barcode Scanner	Honeywell 3603, 1D/2D barcode scanner
WIFI	Support 2.4/5GHz A/B/G/N/AC, support wireless roaming	Audio System	Support
Camera	Rear 8 MP	3D Accelerometer	Support
SIM	NANO 4G dual SIM card slots: Support SD card, Maximum 128GB, Choose two from three with T card	3D Gyroscope	Not Support
Bluetooth	BT 4.0	Electronic Compass	Support
4G	4G dual SIM card slots: 1. GSM: B5/850;B8/900;B3/1800;B2/1900; 2. 3G: WCDMA B1/2100;B2/1900;B5/850;B8/900; Optional B4 3. FDD-LTE, FDD LTE B1/B2/B3/B4/B5/B7/B8/B12/B13/B17/B20 4. TDD: B38/B39/B40/B41	Distance Sensor	Support
GPS	GPS, GLONASS	Light Sensor	Support
		Barometer	Not Support
		Video Encoding Format	3gp/H.265/MPEG4
		Vibration Motor	Support
		Microphone	Support
		Pilot Lamp	Support Color: Red, Blue and Green
		Button	Four on the side: Volume, Two Scanning buttom, Power Button

Environment

Operating Temp. -10°C~-50°C

Storage Temp. -20°C~-60°C

Optional

<p>RFID</p> <p>Support, 26dB, Maximum distance 3m</p> <p>Preset frequency:</p> <ul style="list-style-type: none"> • FCC (NA, SA) 917.4 – 927.2 MHz • ETSI (EU) 865.6 – 867.6 MHz • TRAI (India) 865 – 867 MHz • KCC (Korea) 917– 923.5 MHz • MIC (Japan) 916.8 – 923.4 MHz • ACMA (Australia) 920 – 926 MHz • SRRC-MII (P.R.China) 920.1– 924.9 MHz • ‘Open’ (Customizable channel plan; 859 – 873 MHz and 915 – 930 MHz) <p>Support Agreement: EPCglobal UHF Class 1 Gen 2 / ISO 18000-6C</p> <p>Loading Speed: Up to 200 tags/sec reading 96-bit EPC</p> <p>Output: 18-26 dBm</p> <p>Accuracy: +/- 1dB</p> <p>Flat: +/- 0.2dB</p> <p>Receiving sensitivity: < -70dBm</p> <p>Inventory Label peak speed: > 50 pg/s</p> <p>Label cache: 200 Label @ 96 bit EPC</p> <p>Label RSSI: Support</p>	<p>LF</p> <p>134.2KHz FDX-B and HDX according to ISO/IEC11784/5</p> <p>NFC</p> <p>NXP NQ310</p> <p>Spare Battery</p> <p>500 mAh spare battery</p> <p>Desktop Adapter</p> <p>Support</p>
---	---

Product Six Views:

