

PDS-GS1202T-YK

12.1" LCD display



Features:

- 12.1" capacitive touch LCD display
- Resolution 1024*768
- 1*VGA, 1*HD, 1*DVI
- 1*Menu control button

Specifications:

Display

LCD Type	12.1" LCD screen	Contrast Ratio	1000: 1
Resolution	1024*768	Display Ratio	4: 3
Luminance	350 cd/m ²		

Touch Screen

Touchscreen Type	capacitive touch screen	Hardness	≥6H
Light Transmission	≥85%		

I/O Ports

VGA	1*VGA	Power Socket	DC power input (optional aviation plug)
HD	1*HD	Headphone Jack	1*line-out+1mic-in
DVI	1*DVI	Speaker	optional

OSD Language

Menu Language	Chinese, English, German, French, Italian, Korean, Portuguese
---------------	---

Power

Power Input	12V DC input (9~36V wide voltage module optional, standard 12/5A power adapter)
-------------	---

Environment

Shock Protection	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration	Operating Temp.	-10°C~60°C Surface air flow
Vibration Protection	10g acceleration, 11ms period	Storage Temp.	-20°C~70°C
Reliability	MTBF≥30000h; MTTR≤0.5h	Humidity	95% @40°C, no condensation
		IP Rating	Front panel IP65

Mechanical

Dimension (WxHxD)	291*230*45mm	Material	Aluminum alloy panel all metal design
Weight	2.11kg/3.4kg(N.W./G.W.)	Mounting	VESA installation: 100*100mm, 75*75mm Embedded installation: 274.9*214.2mm
Color	black		

Dimensions:

