

# PDS-GS1501T-SF

15" Rugged Industrial Panel Display



## Features:

- 15" TFT LED LCD screen
- Integrated capacitive touchscreen
- Rugged all-aluminum construction for a wide range of applications
- Long life and high reliability
- Fast response time, no smear, no jitter
- Ultra-wide viewing angle for clear picture quality at large angles

## Specifications:

### Display

LCD Type	15" TFT LED	Contrast Ratio	1000:1
Resolution	1024*768	Touchscreen Type	capacitive touch screen
Luminance	350 cd/m <sup>2</sup>	Display Input	VGA HD DVI

### Power

Power Input	100~240VAC/50~60Hz (with adapter)/12V DC input
-------------	--

### I/O Ports

USB	Touch screen interface
-----	------------------------

### Environment

Shock Protection	5-19Hz/1.0mm amplitude; 19-200Hz/1.0g acceleration	Operating Temp.	-10°C~60°C
Vibration Protection	10g acceleration, 11ms period	Storage Temp.	-20°C~70°C
Reliability	MTBF≥50000h; MTTR≤0.5h	Humidity	95% @40°C, no condensation
		IP Rating	Front panel IP65 (optional)

### Mechanical

Dimension (WxHxD)	376*299.5*39mm	Mounting	Aluminum alloy panel fanless design
Weight	1.0kg/2.1kg(N.W./G.W.)	Color	Black

Dimensions:

